

Ducting

BLAUBERG 3 ZERO POLYESTER NUDE CORE DUCT

Product Code	Size
BLADUCT100-3	100 mm×6 m
BLADUCT125-3	125 mm×6 m
BLADUCT150-3	150 mm×6 m
BLADUCT200-3	200 mm×6 m
BLADUCT250-3	250 mm×6 m
BLADUCT300-3	300 mm×6 m
BLADUCT350-3	350 mm×6 m
BLADUCT400-3	400 mm×6 m
BLADUCT450-3	450 mm×6 m
BLADUCT500-3	500 mm×6 m

All ducting meets the requirements of Australian Standards 4254 and the building codes of Australia for domestic and commercial air handling systems



BLAUBERG 4 ZERO ALUMINIUM/POLYESTER NUDE CORE DUCT

Product Code	Size
BLADUCT100-4	100 mm×6 m
BLADUCT125-4	125 mm×6 m
BLADUCT150-4	150 mm×6 m
BLADUCT200-4	200 mm×6 m
BLADUCT250-4	250 mm×6 m
BLADUCT300-4	300 mm×6 m
BLADUCT350-4	350 mm×6 m
BLADUCT400-4	400 mm×6 m
BLADUCT450-4	450 mm×6 m
BLADUCT500-4	500 mm×6 m

All ducting meets the requirements of Australian Standards 4254 and the building codes of Australia for domestic and commercial air handling systems



BLAUBERG 3 ZERO – R0.6 POLYESTER INSULATED DUCT

Product Code	Size
BLADUCT100-R0.6	100 mm×6 m
BLADUCT125-R0.6	125 mm×6 m
BLADUCT150-R0.6	150 mm×6 m
BLADUCT200-R0.6	200 mm×6 m
BLADUCT250-R0.6	250 mm×6 m
BLADUCT300-R0.6	300 mm×6 m
BLADUCT350-R0.6	350 mm×6 m
BLADUCT400-R0.6	400 mm×6 m
BLADUCT450-R0.6	450 mm×6 m
BLADUCT500-R0.6	500 mm×6 m

All ducting meets the requirements of Australian Standards 4254 and the building codes of Australia for domestic and commercial air handling systems



BLAUBERG 3 ZERO – R1.0 POLYESTER INSULATED DUCT

Product Code	Size
BLADUCT100-R1.0	100 mm×6 m
BLADUCT125-R1.0	125 mm×6 m
BLADUCT150-R1.0	150 mm×6 m
BLADUCT200-R1.0	200 mm×6 m
BLADUCT250-R1.0	250 mm×6 m
BLADUCT300-R1.0	300 mm×6 m
BLADUCT350-R1.0	350 mm×6 m
BLADUCT400-R1.0	400 mm×6 m
BLADUCT450-R1.0	450 mm×6 m
BLADUCT500-R1.0	500 mm×6 m

All ducting meets the requirements of Australian Standards 4254 and the building codes of Australia for domestic and commercial air handling systems

BLAUBERG 3 ZERO – R1.5 POLYESTER INSULATED DUCT

Product Code	Size
BLADUCT100-R1.5	100 mm×6 m
BLADUCT125-R1.5	125 mm×6 m
BLADUCT150-R1.5	150 mm×6 m
BLADUCT200-R1.5	200 mm×6 m
BLADUCT250-R1.5	250 mm×6 m
BLADUCT300-R1.5	300 mm×6 m
BLADUCT350-R1.5	350 mm×6 m
BLADUCT400-R1.5	400 mm×6 m
BLADUCT450-R1.5	450 mm×6 m
BLADUCT500-R1.5	500 mm×6 m

All ducting meets the requirements of Australian Standards 4254 and the building codes of Australia for domestic and commercial air handling systems

BLAUBERG – SEMI RIGID ALUMINIUM DUCT

Product Code	Size
BLADUCTAN100	100 mm×3 m
BLADUCTAN125	125 mm×3 m
BLADUCTAN150	150 mm×3 m
BLADUCTAN200	200 mm×3 m

All ducting meets the requirements of Australian Standards 4254 and the building codes of Australia for domestic and commercial air handling systems

BLAUBERG – FLEXIBLE AIR DUCT BLAUFLEX PVC

- o Made of 65 micron thick white PVC film reinforced with steel wire frame
- o Temperature range, °C : -18 ... +70

Model	Ø d	l (Length)
BlauFlex PVC/102/3	102 mm	3 m
BlauFlex PVC/127/4	127 mm	4 m
BlauFlex PVC/152/5	152 mm	5 m

Product Code	Size
BLABDCT1003PVC	100 mm×3 m PVC DUCT
BLABDCT1254PVC	125 mm×4 m PVC DUCT
BLABDCT1505PVC	150 mm×5 m PVC DUCT

All ducting meets the requirements of Australian Standards 4254 and the building codes of Australia for domestic and commercial air handling systems

