



Turbo EC 315

Mixed-flow inline fans with EC-motors

- Sound pressure level LpA at 3 m: 55
- Impeller type: Mixed-flow
- Casing material: Plastic
- Installation in any position




	Unit of measurement	Turbo EC 315
Connected air duct size	mm	315
Phases	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50/60
Rated power	W	284
Unit current	A	1.25
Maximum airflow	m ³ /h	1970
Sound pressure level LpA at 3 m	dB(A)	55
Weight	kg	11.95
Transported air temperature (max)	°C	55
Transported air temperature (min)	°C	-25
Ingress protection rating	-	IPX4
Impeller material	-	Plastic



Dimensions

ØD	B	H	L	ØD1
308.5	360	423	443	323



Ecodesign

Trademark	Blauberg
Model	Turbo EC 315
Type of drive installed	Integrated VSD
Type of heat recovery system	None
Nominal flow rate (m ³ /s)	0.31
Nominal external pressure (Pa)	371
Maximum external leakage rates (%)	2.7
Static efficiency (%)	46.6
Declared typology	NRVU UVU
Effective electric power input (kW)	0.283
Sound power level (dB(A))	75